

Safety Data Sheet

Issue date 15-Jul-2015 Version 1

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product name CHAMPION SPRAYON VISTA MAX ALL-WEATHER WINDSHIELD CLEANER

Chemical name 7-7893-2

Other means of identification

Product code FG 438-5124-5 Synonyms Windshield Cleaner

Recommended use of the chemical and restrictions on use

Recommended Use Windshields.

Uses advised against DO NOT USE ON FLOORS See directions for use on product's label.

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressChase Products Co.Chase Products Co.2727 Gardner Road2727 Gardner RoadBroadview, IL 60155Broadview, IL 60155708-273-1121708-273-1121

Emergency Telephone Number

Company Phone Number 708-865-1000 **24 Hour Emergency Phone Number** 1-800-255-3924

Emergency telephone ChemTel 1-800-255-3924

2. Hazards Identification

Classification

Serious eye damage/eye irritation	Category 2A
FLAMMABLE AEROSOLS	Category 2
Gases Under Pressure	liquefied gas

Label Elements

EMERGENCY OVERVIEW

Warning

hazard statements

Causes serious eye irritation

Flammable Aerosol

aerosolized.

Contains gas under pressure; may explode if heated



Appearance Clear liquid that will be

Physical State Aerosol

Odor Mild perfumed odor

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling

Wear eye protection and face protection.

Keep away from heat, sparks, open flames and hot surfaces. — No smoking

Do not spray on an open flame or other ignition source

Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place Do not expose to temperatures exceeding 122 °F (50 °C)

Hazards not otherwise classified (HNOC)

Other Information

1.15% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/information on Ingredients

Common NameWindshield Cleaner.SynonymsWindshield Cleaner.Chemical FamilyMIXTURES.

Formula 7-7893-2

Chemical nature Aqueous solution of organic solvent.

Chemical name	CAS No	weight-%	Trade secret
Water	7732-18-5	70-75	*
Ethyl alcohol	64-17-5	15-20	*
2-Butoxyethanol	111-76-2	1-5	*
N-Butane	106-97-8	1-5	*
Propane	74-98-6	1-5	*

Chemical Additions

Hazardous components according to OSHA, are listed when present at 1% or greater. Carcinoges are listed when present at 0.1% or greater.

4. First aid measures

FIRST AID MEASURES

Eye Contact Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact

lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control

center or doctor for treatment advice.

Skin contactWash skin with soap and water. In the case of skin irritation or allergic reactions see a

physician.

inhalation If overcome by vapor, move person to fresh air. Restore respiration if necessary. Get

medical attention if injury develops.

INGESTION Ingestion from an aerosol product is unlikely to occur.

Most important symptoms and effects, both acute and delayed

Symptoms Acute, Deliberate inhalation of concentrated vapor or mist may cause headaches.

Prolonged and repeated contact with the eyes may cause mild irritation. Chronic:

2-butoxyethanol may cause hemolysis of the blood cells leading to possible liver and kidney

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

damage.

Indication of any immediate medical attention and special treatment needed

Note to physicians None needed.

5. Fire-fighting measures

Suitable extinguishing media

Dry chemical, CO2 or water spray.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

Hazardous combustion products Thermal decomposition may release carbon monoxide and carbon dioxide.

Explosion data

Sensitivity to Mechanical Impact Contents under pressure, keep away from heat and open flame.

Sensitivity to Static Discharge Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For emergency responders Remove all sources of ignition.

Environmental Precautions

Environmental Precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Provide adequate ventilation to area being treated. Soak up spills with chemically inert,

absorbent material.

Methods for cleaning upClean contaminated surface thoroughly.

7. Handling and Storage

Precautions for safe handling

Advice on safe handlingDo not deliberately inhale vapor or spray mist. Avoid getting spray into eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store in a cool, dry place away from heat and open flame. Keep out of reach of children.

AEROSOL STORAGE LEVEL I (NFPA-30B).

Incompatible Materials Avoid heat, open flame and contact with strong oxidizers.

8. Exposure Controls/Personal Protection

Control parameters

Exposure guidelines See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m³

Appropriate engineering controls

Use with adequate general or local exhaust ventilation. **Engineering controls**

Individual protection measures, such as personal protective equipment

Eye/face Protection Conventional eyeglasses to guard against splashing.

Skin and Body Protection Rubber, vinyl or household type gloves.

Respiratory protection None required if used in a well-ventilated area .

General hygiene considerations Wash hands thoroughly after handling.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State Aerosol

Appearance Clear liquid that will be aerosolized. Odor Mild perfumed odor Color No information available clear Odor threshold

Remarks • Method **Property** Values рΗ 10.25 No information available Melting point/freezing point Not applicable No information available Water 212 °F/100 °C Boiling point/boiling range No information available Flash Point Not Available. This is an aerosol No information available

product for which Flame Projection is 0 inches. Temperatures above 120 F

may cause cans to burst.

Evaporation Rate Faster than butyl acetate

No information available Flammability (solid, gas) No information available Flammability Limits in Air No information available

Upper flammability limits Not available **Lower Flammability Limit** Not available

No information available Vapor pressure No information available **Vapor Density Relative Density** 0.965 concentrate No information available

Soluble in water Water solubility

Solubility in other solvents No information available **Partition coefficient** No information available No information available **Autoignition Temperature**

Decomposition temperature

Kinematic viscosity
Dynamic viscosity

No information available No information available No information available

Explosive properties No information available Oxidizing properties No information available

Other Information

Softening point No information available

Molecular weight No information available

VOC content (%) 26.08 **Density** 8.04 lb/gal

Bulk Density

No information available

10. Stability and Reactivity

Reactivity

Not applicable Not applicable

Chemical stability

Stable.

Possibility of hazardous reactions

Temperatures above 130 °F may cause cans to burst with force.

hazardous polymerization Hazardous polymerization does not occur.

Conditions to Avoid

Temperatures above 122 °F (50 °C).

Incompatible Materials

Avoid heat, open flame and contact with strong oxidizers.

Hazardous decomposition products

Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

11. Toxicological Information

Information on likely routes of exposure

Primary routes of entry: Eye contact, skin contact, inhalation, ingestion (possible, but

consider unlikely).

inhalation Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Eye Contact Can cause irritation after contact with eyes.

Skin contact May cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily.

Frequent or wide spread contact may results on skin absorption of potentially harmful

amounts.

INGESTIONThis is an aerosol product, ingestion is unlikely to occur. 2-Butoxyethanol may cause red

blood cell hemolysis and possible liver and kidney damage.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
Ethyl alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
2-Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
N-Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Propane 74-98-6	-	-	= 658 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationMay cause skin irritation after contact with skin. 2-Butoxyethanol penetrates skin readily.

Frequent or wide spread contact may results on skin absorption of potentially harmful

amounts.

Serious eye damage/eye irritation Can cause irritation after contact with the eyes.

corrosivityNot applicable.sensitizationNo a skin sensitizer.Germ Cell MutagenicityNo information available.

carcinogenicity Ethanol has been shown to be carcinogenic in long-term studies only when consumed as

alcoholic beverage. Not known chronic effects based on available information.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration Hazard Deliberate inhalation of concentrated vapor or mist may cause headache, dizziness and

nausea.

Numerical measures of toxicity - Product Information

Unknown acute toxicity 1.15% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 10275 mg/kg

 ATEmix (dermal)
 32738 mg/kg

 ATEmix (inhalation-gas)
 20775 mg/l

 ATEmix (inhalation-dust/mist)
 41.9 mg/l

 ATEmix (inhalation-vapor)
 626 mg/l

12. Ecological Information

This product does not contain marine pollutants.

ecotoxicity

5.15% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Ethyl alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through		9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50
2-Butoxyethanol 111-76-2		1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50		1000: 48 h Daphnia magna mg/L EC50 1698 - 1940: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name Partition coefficient

Ethyl alcohol 64-17-5	-0.32
2-Butoxyethanol 111-76-2	0.81
N-Butane 106-97-8	2.89
Propane 74-98-6	2.3

Other adverse effects No information available

13. Disposal Considerations

Waste treatment methods

Dispose of in accordance with federal, state and local regulations. Disposal of wastes

Contaminated packaging Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate

container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your

local solid waste agency for disposal instructions.

Chemical name	California Hazardous Waste Status
Ethyl alcohol	Toxic
64-17-5	Ignitable

14. Transport Information

DOT Limited quantity (LQ) Windshield Cleaner

UN/ID no UN1950

Proper Shipping Name Limited quantity (LQ)

Hazard Class

This product does not contain marine pollutants. Marine pollutant

15. Regulatory information

International Inventories

TSCA All ingredients of this product are listed or are excluded from listing under the U.S. Toxic

Subtances Control Act (TSCA) Chemical Substance Inventory.

DSL All ingredients are listed or are excluded from listing on the DSL.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold
			Values %

2-Butoxyethanol - 111-76-2	111-76-2	1-5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Water 7732-18-5			X
Ethyl alcohol 64-17-5	Х	X	X
2-Butoxyethanol 111-76-2	X	X	X
N-Butane 106-97-8	X	X	X
Propane 74-98-6	X	X	X

U.S. EPA Label information

EPA Pesticide registration number Not applicable

16. Other information				
NFPA	Health Hazards 1	Flammability 1	Instability 1	Physical and chemical properties Not applicable
<u>HMIS</u>	Health Hazards 1	Flammability 2	Physical Hazards 1	Personal Protection B - Eyes and hands protection

Prepared by Regulatory Department

Issue date 15-Jul-2015

Revision note

This SDS supersedes a previous SDS dated September 10, 2014.

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet