



STEADY FLOW

BIO-ENZYMATIC DRAIN CLEANER AND SOIL REMOVER

Steady Flow (SF) is a concentrated liquid drain opener for use in grease traps, sink drains, garbage disposals, shower stalls and bathtubs, holding tanks, portable toilets and outhouses, septic tanks and tile fields. SF contains living bacteria that naturally digest unwanted solids such as grease, fats, proteins, carbohydrates and sugars. SF quickly eliminates offensive odors by destroying the source.

Physical Properties (Typical)

Appearance

Density

Odor

pH (1% solution)

Specific Gravity

Opaque White liquid 8.4 pounds/gallon Lemon

7

1.0 (Water = 1.00)





Directions for Use

- <u>Ultrafiltration and Reverse Osmosis Membrane Clean in Place</u> Circulate a 0.5% 2% solution for up to 1 hour depending on the design of the equipment and soil load
- <u>Grease Trap</u> Initial Treatment Pour 32 oz. (946 ml) SF into the opening closest to the trap at the beginning of the longest time period the trap will not be used
- Grease Trap Maintenance Use 4 oz. (118 ml) SF daily (use more for larger grease traps)
- Sink Drain Use 4 oz. (118 ml) SF twice a week (use more for larger drains)
- Garbage Disposal Use 2 oz. (59.1 ml) SF once a week
- Shower Stalls/Bathtub Drain Use 4 oz. (118 ml) SF once a week
- <u>Recreational Vehicle & Marine Holding Tank</u> Use 3 oz. (88.7 ml) SF per 1 gal. (3.79 L) of liquid in holding tank
- <u>Portable Toilet/Outhouse</u> Add 32 oz. (0.95 L) SF to solids to deodorize and aid in digestion
- Septic Tank Pour 8 oz. (237 ml) SF directly into toilet once a week, flush
- <u>Tile Field</u> Add 1 gal. (3.79 L) SF directly to distribution box after tank has been treated, repeat as needed

Steady Flow does not contain any nonylphenol ethoxylates (NPEs). It is better for the environment and is subject to fewer regulatory restrictions than NPE-containing products.

Steady Flow does not contain any phosphates.

Available sizes: 5 gal. & 55 gal.