



SUPER STRIP

CONCENTRATED FLOOR WAX STRIPPER WITH ADVANCED FORMULA

Super Strip (SS) is a concentrated floor stripper with an advanced formula that liquefies old finish in minutes. SS quickly penetrates multiple coats of metal interlock or environmentally sustainable floor finishes. SS is easy to use and works with minimal odor.

Physical Properties (Typical)

Appearance	Opaque white liquid
Density	8.6 pounds/gallon
Odor	Mild to none
pH (as is)	8
Solubility in water	Complete at recommended dilutions
Specific Gravity	1.03 (Water = 1.00)



Directions

Usage

Normal Stripping: Use 1 part to 5 parts HOT water

Heavy Buildup: Use 1 part 2 parts HOT water



Procedure

Asphalt tile: Check small area for colorfastness before applying SS

- Apply hot solution to floor with mop or floor scrubber and strip pad
- Allow solution to stand for 5 minutes
 - Keep floor wet; do not allow to dry
- When floor finish is liquefied, remove with mop or wet vac
- With heavy buildup, loosen softened finish with stiff brush or broom before removal
- Rinse floor twice
- Let dry before applying new finish

Super Strip does not contain any nonylphenol ethoxylates (NPEs). It is better for the environment and is subject to fewer regulatory restrictions than similar NPE-containing products.

Available sizes: 1 gal.

Complete Cleaning Solutions