



ULTRA KOTE

METAL INTERLOCK FLOOR FINISH

ULTRA KOTE (UK) is a superior metal interlock floor finish formulated for super durability, hardness and high gloss. UK is slip-resistant, black mark resistant and shines without buffing. UK will not discolor or powder. UK may be burnished. UK is recommended for use on asphalt tile, ceramic tile, concrete, linoleum, rubber, sealed wood, terrazzo, vinyl and vinyl asbestos floors.

Physical Properties (Typical)

Appearance	Opaque white liquid
Density	8.6 pounds/gallon
Odor	Mild to none
pH (as is)	8
Solubility in water	Complete at recommended dilutions
Specific Gravity	1.03 (Water = 1.00)



Directions for Use

Use 1 gal to cover 1,500 - 2,500 sq. ft. of floor area

- Clean the floor thoroughly with DEVERE WOW or LIQUID CLEANER followed by a complete rinse
- Strip the old finish, if necessary, with DEVERE SUPER STRIP
- Allow the floor to dry completely
- Using a clean mop or applicator designed for floor finishes, spread UK evenly with long strokes; avoid going over freshly finished areas
- Allow the floor to dry completely (30 to 40 minutes) before applying a second coat
- Traffic lanes and other worn areas can be re-coated

NOTE: Use a high speed burnisher if a "wet look" is desired

Ultra Kote does not contain any nonylphenol ethoxylates (NPEs). It is better for the environment and is subject to fewer regulatory restrictions than similar NPE-containing products.

Ultra Kote does not contain any phosphates.

Available sizes: 1 gal. & 5 gal.

Complete Cleaning Solutions